

# Multi-Link Systems

The Multi-Link integrated quick connect couplings come in units of 1 to 5 outlets.

## eSafe™

### TECHNICAL DATA

Temperature range: ..... -20°C – 100°C (-4°F – 212°F)

Max. working pressure:..... 16 bar (230 PSI)

Material: ..... Zinc-plated steel/zinc




CEJN Safety

		Part No.	Connection
<b>SERIES 310</b>	2-outlet unit	19 902 9922	G 1/2"
	3-outlet unit	19 902 9923	G 1/2"

		Part No.	Connection
<b>SERIES 315</b>	2-outlet unit	19 902 9972	G 1/2"
	3-outlet unit	19 902 9973	G 1/2"
	4-outlet unit	19 902 9974	G 1/2"
	5-outlet unit	19 902 9975	G 1/2"

		Part No.	Connection
<b>SERIES 320</b>	2-outlet unit	19 902 9912	G 1/2"
	3-outlet unit	19 902 9913	G 1/2"

		Part No.	Connection
<b>FEMALE ADAPTER</b>	Extension unit G 1/2"	19 902 9990	G 1/2"
	1-outlet unit G 1/2"	19 902 9991	G 1/2"
	2-outlet unit G 1/2"	19 902 9992	G 1/2"
	3-outlet unit G 1/2"	19 902 9993	G 1/2"
	4-outlet unit G 1/2"	19 902 9994	G 1/2"



		Part No.	Connection
<b>SERIE 300 ESAFE</b>	Extension unit	19 902 9000	G 1/2"
	1-outlet unit	19 902 9001	G 1/2"
	2-outlet unit	19 902 9002	G 1/2"
	3-outlet unit	19 902 9003	G 1/2"
	4-outlet unit	19 902 9004	G 1/2"

		Part No.	Connection
<b>SERIE 310 ESAFE</b>	Extension unit	19 902 9100	G 1/2"
	1-outlet unit	19 902 9101	G 1/2"
	2-outlet unit	19 902 9102	G 1/2"
	3-outlet unit	19 902 9103	G 1/2"
	4-outlet unit	19 902 9104	G 1/2"

		Part No.	Connection
<b>SERIE 315 ESAFE</b>	Extension unit	19 902 9150	G 1/2"
	1-outlet unit	19 902 9151	G 1/2"
	2-outlet unit	19 902 9152	G 1/2"
	3-outlet unit	19 902 9153	G 1/2"
	4-outlet unit	19 902 9154	G 1/2"

		Part No.	Connection
<b>SERIE 320 ESAFE</b>	Extension unit	19 902 9200	G 1/2"
	1-outlet unit	19 902 9201	G 1/2"
	2-outlet unit	19 902 9202	G 1/2"
	3-outlet unit	19 902 9203	G 1/2"
	4-outlet unit	19 902 9204	G 1/2"
	5-outlet unit	19 902 9205	G 1/2"