Specifications

SQUARE D



Mini circuit breaker, E-Frame, 50A, 3 pole, 480Y/277 VAC, 25 kA max, bolt on

EDB34050

Main

| Range Of Product | 125 A Frame EDB-EGB-EJB |
|---------------------------|---------------------------|
| Product Or Component Type | Miniature circuit-breaker |
| Device Short Name | EDB |
| Module Type | E-Frame |
| Trip Unit Rating | 1800 A |

Complementary

| Complementary | |
|-----------------------------|--|
| Line Rated Current | 50 A |
| Maximum Operating Voltage | 480Y/277 V AC |
| Awg Gauge | AWG 12AWG 2/0 aluminium AWG 14AWG 2/0 copper |
| Breaking Capacity | 18 kA 277 V AC 25 kA 240 V AC 18 kA 480Y/277 V AC 25 kA 120 V AC 25 kA 120/240 V AC |
| Circuit Breaker Application | HACR rated HID rated |
| Electrical Connection | Lugs aluminium |
| Holding Current | 630 A |
| Local Signalling | Trip indicator |
| Mounting Mode | Bolt-on |
| Number Of Poles | 3 |
| Number Of Spaces | 3 |
| Number Of Spaces Required | 3 |
| Product Destination | NF panelboard |
| Protection Type | Short-circuit Overload |
| Trip Unit Technology | Thermal-magnetic |
| Breaking Capacity Code | D |
| Tightening Torque | 34.52 lbf.in (3.9 N.m) 0.000.01 in² (2.56 mm²) (AWG 14AWG 10) 49.56 lbf.in (5.6 N.m) 0.020.11 in² (1070 mm²) (AWG 8AWG 2/0) |
| Height | 5.66 in (143.76 mm) |
| Width | 2.94 in (74.68 mm) |

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

| Depth | 4.05 in (102.87 mm) |
|------------|---------------------|
| Net Weight | 4 lb(US) (1.81 kg) |

Environment

| Product Certifications | cULus |
|--|----------------|
| Ambient Air Temperature For Operation | 104 °F (40 °C) |

Ordering and shipping details

| Category | US10DE200931 |
|-------------------|--------------|
| Discount Schedule | 0DE2 |
| Gtin | 785901875314 |
| Returnability | Yes |
| Country Of Origin | MX |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|----------------------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 4.80 in (12.2 cm) |
| Package 1 Width | 6.42 in (16.3 cm) |
| Package 1 Length | 9.88 in (25.1 cm) |
| Package 1 Weight | 3.53 lb(US) (1.6 kg) |

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

| Mercury Free | |
|----------------------------|--|
| Rohs Exemption Information | Yes |
| | |
| Reach Regulation | REACh Declaration |
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| | Product out of China RoHS scope. Substance declaration for your information. |